



# Gaysha

## Clearmac® Quartz quartz carpet flooring system



Clearmac® Quartz is a seamless quartz flooring system, ideal for houses, offices and showrooms. It can also be used in outside spaces.

Pleasingly tactile and attractive, Clearmac® Quartz comprises coloured or natural quartz grains, bonded in epoxy or polyurethane resin to create a wall to wall modern flooring surface.

The open surface of the quartz means it contains millions of tiny air pockets, creating a warm and soft surface that is cosy and welcoming to bare feet.

Clearmac® Quartz provides the warmth and comfort of a traditional carpet but is far easier to keep clean and lasts for many years.

### Typical uses and applications

Clearmac® Quartz can be readily installed on a wide selection of surfaces and can be opened for use typically within 24 hours of application.


The surface is ideal for most internal uses, with a UV resistant grade available for use outdoors and in rooms with large windows. For bathrooms, toilets and kitchens a hygienic grade is available which is fully sealed.

### Colours

Clearmac® Quartz is available in four different granule sizes and over 1000 colours. These colours can be mixed and combined to create endless design possibilities.

This flexibility makes it easy to incorporate bespoke designs, logos and text in your flooring.

A small selection of the colours available is shown to the right.



## Clearmac® Quartz flooring system



Easy to clean  
Warm and soft  
to the touch  
Endless colour  
possibilities

### Performance

Clearmac® Quartz is a unique and visually striking flooring system designed for both interior and exterior application. Composed of coloured quartz crystals bonded in resin, it is ideal for houses, offices, showrooms, health spas and it can also be applied in outside areas. The surface is seamless, wear resistant, easy to clean and provides a soft inviting finish that feels warm to the touch.

Clearmac® Quartz is available in over 1000 colours making it ideal for creating surfaces incorporating corporate logos and designs.

### Installation

The aggregate and binder system are mixed on site immediately prior to laying.

An appropriate primer for the substrate is applied and allowed to dry. The mixed aggregate is then spread over the surface and evened out with a trowel to a thickness of 6-10mm.

Depending on the required final finish a suitable top coat is then applied. For hygienic reasons rooms such as toilets, kitchens or bathrooms require an additional sealing of the quartz carpet.

### Maintenance

Rather than remaining on the surface, dust will disappear between the pores of the flooring until it can be easily removed with a normal vacuum cleaner. In the case of mud or heavy soiling, allow to dry and then remove with a brush. If necessary mop or wet vacuum the surface.

It is recommended that you clean the stone carpet once or twice a year with a powerful wet cleaner/ carpet cleaner.

### Preparation

The substrate must be clean, dry, and free of dust and grease, cement-based substrates must be at least 21 days old.

Our detailed specification advice sheets are downloadable from our website or can be requested by email or phone.

Before every new commission our Survey Department will visit and prepare a pre-installation report and are available to offer advice and answer your questions throughout the process.

### Quality Assurance

Clearmac® Quartz flooring is supplied and laid within ISO 9001 quality management systems certified by BSI.

### Health and Safety

All of the materials used to install Clearmac® Quartz are non-flammable and chemically stable. The surface is cold-applied and therefore has no requirement for the use of heating equipment or hot materials. The surface requires twenty four hours to cure for foot traffic.

### Further Information

For free advice and support or to request our colour samples contact us on 01322 340350 or visit [www.gayshasurfaces.co.uk](http://www.gayshasurfaces.co.uk)